



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

**SAFETY DATA SHEET**

**1. Product and Company Identification**

**Product Name:** Haynes Lubrifilm Spray  
NSF H1  
**Product Code:** 60  
**Product Type:** Aerosol  
**Product Use:** Industrial Lubricant

**Manufacturer:** Haynes Manufacturing Co  
**Address:** 24142 Detroit Road  
Westlake, OH 44145 USA

**Revision Date:** 04/22/15  
**Phone:** 440.871.2188

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

**2. Hazard Identification**

**Classification of substance or mixture:**

Flammable Aerosols	Category 1
Gases under pressure	Liquefied gas
Skin Irritation	Category 2
Specific target organ (single exposure)	Category 3
Aspiration Hazard	Category 1

**Pictograms:**



**Signal Word: Danger**

H222 Extremely Flammable aerosol  
H280 Contains gases under pressure; may explode if heated  
H315 Causes skin irritation  
H336 May cause drowsiness or dizziness  
H304 May be fatal if swallowed and enter airways

**Precautionary Statements:**



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

**Prevention**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/ spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in well-ventilated place
- P280 Wear protective gloves

**Response:**

- P301+P310 If Swallowed: Immediately call a poison center or doctor
- P331 Do NOT induce vomiting
- P304+P340 If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell.
- P302+P352 If on skin: Wash with plenty of soap and water
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P403 Store in well ventilated place
- P405 Store locked up
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations.

**3. Composition information on ingredients**

Ingredients	CAS #	Percent	Trade Secret
Liquefied Petroleum Gas	68476-86-8	15-30 %	*
Petroleum Grease	8009-03-8	70-95%	*
Isoparaffinic Hydrocarbon	64741-66-8	8-15%	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. First Aid Measures**

**Eye Contact:**

Flush with warm water for 15 minutes. Seek medical attention.

**Skin Contact:**

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

**Inhalation:**



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary.  
Contact a physician.

**Ingestion:**

Do not induce vomiting. Get medical attention immediately. DO NOT GIVE AN UNCONCIOUS OR CONVULSING PERSON ANYTHING BY MOUTH!

## 5. Fire Fighting Measures

**Flash Point:** Flash point of propellant <0 degrees F.

**Flammable limits in air, % by volume:**

**Upper:** 9.5% (VOL.) Gas in air (propellant portion)

**Lower:** 1.8 % (VOL.) Gas in air (propellant portion)

**Extinguishing Media:**

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

**Unusual Fire & Explosion Hazards:**

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

**Special Fire Fighting Procedures:**

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

## 6. Accidental Release Measures

**Spill or Leak Instructions**

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## 7. Handling and Storage



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

**Handling:**

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

**Storage:**

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

**8. Exposure Controls / Personal Protection**

**Protective Equipment:**

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

**Engineering Controls:**

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

**Respiratory Protection:**

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

**Other Suggested Equipment:**

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

**Discretion Advised:**

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

**Exposure guidelines:**

<b>Ingredients</b>	<b>CAS #</b>	<b>Percent</b>	<b>Exposure Limits</b>
Liquefied Petroleum Gas	68476-86-8	15-30 %	OSHA (PEL) 1000 ppm ACGIH TLV 1000 ppm



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

Petroleum Grease(mist)	8009-03-8	70-95%	ACGIH (TWA) 5 mg/m <sup>3</sup> OSHA (TWA) 5 mg/m <sup>3</sup>
Isoparaffinic Hydrocarbon	64741-66-8	8-15%	Supplier 300 ppm

### 9. Physical and Chemical Properties

<b>Appearance:</b> Amber as dispensed from aerosol can.	<b>Odor:</b> Petroluem
<b>Evaporation Rate:</b> Ether = 1 Slower	
<b>PH:</b> NA	<b>Melting/Freezing point:</b> NE
<b>Initial Boiling point and boiling range:</b> NE	<b>Flash Point:</b> Flash point of propellant <0°F
<b>Flammability:</b> NA	<b>Vapor pressure:</b> >30 psi
<b>Vapor density</b> >1 (Air=1)	
<b>Relative density</b> NE	<b>Solubility:</b> negligible
<b>Partition coefficient:</b> NE	<b>Auto-ignition temperature:</b> NE
<b>Decomposition temperature:</b> NE	<b>Viscosity:</b> NA
<b>Flammable limits in air, % by volume: (propellant portion)</b>	
<b>Upper:</b> 9.5%(vol) Gas in Air	
<b>Lower:</b> 1.8% (vol) Gas in Air	

### 10. Stability and Reactivity

<b>Stability:</b> Stable	<b>Conditions to Avoid:</b> Heat, spark, and open flame
<b>Incompatibility:</b> Strong-Oxidizing Agents	
<b>Hazardous Decomposition:</b> Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.	
<b>Hazardous Polymerization:</b> Will not occur	

### 11. Toxicological Information

#### Component Toxicological Information:

#### Information on Toxicological Effects of Components

##### Isoparaffinic Hydrocarbon

##### Acute toxicity

<b>Inhalation</b>	LC50 Rat > 21 mg/l 4 h
<b>Ingestion</b>	LD50 Rat >5,000 mg/kg
<b>Dermal</b>	LD50 Rabbit >2000 mg/kg

##### Propane

**Target Organs:** No systemic or neurotoxic effects were noted in rats exposed to concentrations of propane as high as 12,000 ppm for 28 days.



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

*Reproductive Toxicity:* No adverse reproductive or developmental effects were observed in rats exposed to propane; no observed adverse effect level = 12,000 ppm.

**Isobutane**

*Target Organs:* No systemic or neurotoxic effects were noted in rats exposed to concentrations of isobutane as high as 9,000 ppm for 28 days.

*Reproductive Toxicity:* No adverse developmental effects were observed in rats exposed to concentrations of isobutane as high as 9000 ppm. Fertility and mating indices may have been affected at 9000 ppm but no effects were observed at 3000 ppm

**12. Ecological Information**

**Isoparaffinic Hydrocarbon**

Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Test	Duration	Organism Type	Test Results
Aquatic - Acute Toxicity	96 hour(s)	Oncorhynchus mykiss	LL50 18.4 mg/l: data for the material
Aquatic - Acute Toxicity	48 hour(s)	Daphnia magna	EL50 2.4 mg/l: data for similar materials
Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	NOELR 6.3 mg/l: data for similar materials
Aquatic - Chronic Toxicity	21 day(s)	Daphnia magna	NOEC 0.17 mg/l: data for similar materials
Aquatic - Chronic Toxicity	21 day(s)	Daphnia magna	LOEC 0.32 mg/l: data for similar materials
Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	EL50 29 mg/l: data for similar materials

Petroleum gases will readily evaporate from the surface and would not be expected to have significant adverse effects in the aquatic environment. Classification: No classified hazards.

**13. Disposal Considerations**

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

**14. Transport Information**



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

Aerosols (limited quantity),  
Class 2.1, ERG 126

AIR (IATA)  
Aerosols (limited quantity),  
Class 2.1, ERG 126, UN No. 1950  
Vessel  
Aerosol (Limited Quantity), Class 2.1, UN No 1950

## 15. Regulatory Information

### Environmental Regulations

**SARA 302/304:**

None

**SARA 311/312:**

Immediate ( x ) Delayed ( ) Fire ( x ) Reactive ( ) Sudden Release of Pressure ( x )

**Section 313**

None

**California Prop. 65: None**

All the chemicals used in this product are TSCA listed.  
Check with your local regulators to be sure all local regulations are met.

## 16. Other Information

**Hazard ratings** This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

**NFPA:** Level 3 Aerosol

**HMIS:** Health: 1 Flammability: 4 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

**Note:**

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health



Safety Data Sheet  
**HAYNES LUBRI-FILM SPRAY**  
Haynes Manufacturing Company

standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.