



HAYNES® **PRODUCT INFORMATION**

THE WORLD'S LEADING MANUFACTURER OF PREMIUM FOOD GRADE LUBRICANTS

HAYNES HOMOGENIZER OIL



Haynes Homogenizer Oil is specifically designed as a circulating oil primarily intended for continuous reuse in circulation systems for gears and bearings (non-food contact applications). The oil is water resistant, non-foaming, and heat resistant. Haynes Homogenizer Oil provides superior protection against rust, excellent resistance to oxidation and thermal degradation, and a high level of protection against wear.

Haynes Homogenizer Oil is intended for plain bearings, gears, roller bearings, parallel shaft and bevel gearing. It is suitable as a multipurpose lubricant in systems not subject to shock loading and which do not require extreme pressure performance.

Packaged in 5-gallon pails and 55-gallon drums.

TECHNICAL DATA INFORMATION

TEST	TYPICAL TEST RESULTS
ISO Viscosity Grade	220
Viscosity, ASTM D445, cSt@40°C	218
Viscosity, ASTM D445, cSt@100°C	18.8
Viscosity Index, ASTM D 2270	96
Pour Point, °C, ASTM D 97	-18
Flash Point, °C, ASTM D 92	284

Haynes Manufacturing Company
24142 Detroit Road Westlake, Ohio 44145
U.S.A. & Canada: 800.992.2166 Phone: 440.871.2188 Fax: 440-871-8418
Website: www.haynesmfg.com Email: sales@haynesmfg.com